

Overview

- 2 m sensing range thanks to time of flight principle
- Distance measurement via IO-Link
- Reliable also on very dark and shiny objects
- Manipulation-proof, simple teach-in via qTeach or line teach
- Extended parameterization options and additional diagnostic data via IO-Link
- Infrared laser light source suitable for use in dusty or smoky environments
- Alignment Guide - visible, red light beam for aligning the infrared laser



Picture similar



Technical data

General data

Type	Distance measuring
Version	Time of Flight
Measuring distance Sd	0 ... 2000 mm
Measuring range Mr	2000 mm
Adjustment	Teach-in and IO-Link
Power on indication	LED green
Output indicator	LED yellow
Repeat accuracy	≤ 1.25 ... 1.5
Linearity error	± 10 mm
Beam type	Point
Suppression of reciprocal influence	Yes
Alignment optical axis	< 1,5°
Temperature drift	<0,3 mm/K: <750 mm <0,04 % Sde/K: >750 mm

Light Source

Light source	Pulsed infrared laser diode
Wave length	940 nm
Laser class	1

Electrical data

Response time / release time	< 25 ms (High Speed Mode) < 50 ms (Standard Mode) < 200 ms (High Accuracy Mode)
Voltage supply range +Vs	10 ... 30 VDC
Current consumption max. (no load)	55 mA
Voltage drop Vd	<2.5 VDC
Output circuit	Push-pull / IO-Link
Output current	50 mA
Short circuit protection	Yes

Electrical data

Reverse polarity protection	Yes
-----------------------------	-----

Communication interface

Interface	IO-Link V1.1.4
IO-Link port type	Class A
Baud rate	230.4 kBaud (COM 3)
Cycle time	≥ 0.7 ms
Process data length	48 Bit
Process data structure	Bit 0 = SSC1.1 (distance) Bit 1 = SSC1.2 (distance) Bit 2 = Uncertainty Flag Bit 3 = alarm Bit 8-15 = scale factor Bit 16-47 = 32 Bit measurement

Adjustable parameters	Switching point Switching hysteresis Operation mode Time filters LED status indicators Output logic Deactivate the sensor element Teach-in mode Locator function
-----------------------	--

Additional data	Distance Excess gain Device temperature
-----------------	---

Mechanical data

Width / diameter	8 mm
Height / length	25.1 mm
Depth	15.8 mm
Design	Rectangular
Housing material	Plastic (ASA, PMMA)
Front (optics)	PMMA

Technical data

Mechanical data

Connection types	Cable 4 pin, 2 m
Mechanical mounting	Sleeve smooth (stainless steel)


Ambient conditions

Protection class	IP 67
Operating temperature	-25 ... +50 °C
Storage temperature	-40 ... +70 °C

Ambient conditions


Vibration (sinusoidal)	IEC 60068-2-6:2008 10 g at f = 10 - 2000 Hz, duration 150 min per axis
Shock (semi-sinusoidal)	IEC 60068-2-27:2009 50 g / 11 ms, 10 impulses per axis and direction

Dimension drawing




Repeat accuracy

OT200 High Accuracy Mode



— Ultra-Black — Black — Grey — White

OT200 Standard Mode



— Ultra-Black — Black — Grey — White


Laser warning

CLASS 1 LASER PRODUCT


IEC 60825-1/2014

Complies with 21 CFR 1040.10 and 1040.11 except for conformance with IEC 60825-1 Ed. 3., as described in Laser Notice No. 56, dated May 8, 2019


Connection diagram





Repeat accuracy



Hysteresis curve



Beam characteristic (typically)



Hysteresis curve

